A new version of HadSLP

Rob Allan, Tara Ansell, David Parker, Philip Brohan & Nick Rayner



Outline

- HadSLP version 1.0
- Methodology
- Problems with HadSLP 1.0
- New Marine (I-COADs) and land obs.
- Preliminary results
- Summary and future plans



HadSLP 1

- Gridded 5 x 5 degree product, 1871-1998
- Marine Met Office Marine data bank & COADS
- Land CSIRO, NIWA, CRU, CLIMAT, GHCN, Roseau Mondial, WWR & various sources
- Employed Reduced Space Optimum Interpolation (RSOI, Kaplan et al. 1997) to give globally complete coverage



Methodology

- Quality control (QC)
 - Marine data QC involves comparison to background field.
 - standard gravity, ship deckheights, Paris longitude, reduction to mean sea level, correction for effect of semi-diurnal oscillation, nearest neighbour checks, remove jumps, trends (with reference to station histories)
- Gridding & blending of marine and land obs
- Interpolate over data sparse regions (RSOI)




Problems with HadSLP 1.0

- Spurious trends in the high southern latitudes
 - evident in NCEP reanalysis and ECMWF fields, which were used to create the EOF patterns for the RSOI analysis.
 - Poor spatial coverage in high southern latitudes
- Static error field
- Unable to be readily updated in near real time



HadSLP annual trend





New data sources

- Extend HadSLP to 1850-2001
- Marine
 - I-COADs
- Land
 - digitisation efforts
 - requests for data through international collaboration




Preliminary Results

- Marine observations
 - gridded marine MSLP product, 1826-2001
 - increased coverage in southern mid-latitudes
 - potential to remove spurious trend
- Land observations
 - anticipate to increase number of stations from 719 to, roughly, 1500 (as collected to date).




Improved spatial coverage: 1871



Hadslp
(land & marine)

Number of observations




I-COADs

(marine only)




Improved spatial coverage: 1980



Hadslp
(land & marine)

Number of observations



I-COADs

(marine only)



Future plans

- Include uncertainty estimates
- Updated in near real time
- Include I-COADs wind measurements and potentially CLIWOC records.
- Bring to 24 hour means
- Non-static error field for RSOI analysis

